HD PRO

Series marked for the installer looking for a high-level camera emphasizing the difference in image quality. The Pro series cameras are suitable for indoor and outdoor applications where professional video surveillance is required.



DI-380A-28

20m IR 8MP Fixed Lens Small Dome/Turret Camera

This 4K dome/turret camera presents a stunning 8-megapixel image, equipped with a 2.8mm fixed lens, it is designed for short distance surveillance systems (up to 20m) for both indoor and outdoor scenarios. Featuring 4in1 technology selectable by a protected dipswitch the camera is ideal for Plug & Play over existing analog infrastructure.























MAIN FEATURES

- DI-380A-28 20m IR 8MP Fixed Lens Small Dome/Turret Camera
- Sensor: 1/2.5" 8MP Sensor
- Selectable Output: 8MP: 3840×2160 AHD/TVI/CVI 5MP: 2592×1944 AHD/TVI 4MP: 2560×1440 AHD/TVI/CVI CVBS: 700TVL
- Lens: 2.8mm Mega-Pixel Fixed (89.3°)
- True Day&Night-ICR

- 3D-DNR/BLC
- Illumination: 20m (1 High-Power IR LED)
- IP67
- Weight: 485g
- Power: DC12V/340mA



https://provision-isr.com



SPECIFICATIONS

SPECIFICATIONS		
Video		
Image Sensor	1/2.5" 8MP Sensor	
Image Format	8MP/4MP - 16:9, 5MP - 4:3	
Effective Pixels	3864x2202	
Scanning System	Progressive	
Min. Illumination	Color: 0.01lux@F1.2, AGC ON B/W: 0lux with IR	
Day & Night	True Day&Night-ICR	
Day & Night Modes	Ext/Auto/Day/Night	
Compression		
Resolution	8MP: 3840x2160 AHD/TVI/CVI 5MP: 2592x1944 AHD/TVI 4MP: 2560x1440 AHD/TVI/CVI CVBS: 700TVL	
Frame Rate	8MP @ 12/15FPS, 5MP @ 20FPS, 4MP @ 25/30FPS, CVBS @ 25/30FPS	
Image		
Backlight Compensation	BLC	
S/N Ratio	≥52dB (AGC OFF)	
Privacy Zone	no	
Noise Reduction	3D-DNR	
Image Enhancement	BLC	
On Screen Data		
CoC Support	Yes	

On Screen Data	
CoC Support	Yes
OSD Menu	Available via CoC Only

Lens	
Field of View	2.8mm Mega-Pixel Fixed (89.3°)
Iris	Fixed Iris
Lens Mount	M12 Mount

DI-380A-28



Connectivity	
Audio Connectivity	N/A

Housing	
Illumination	20m (1 High-Power IR LED)
Bracket	3-Axis Bracket
Protection Rate	IP67
Dimensions	Ф97*82.6mm
Weight (gross)	485g
Power	DC12V/340mA
Work Environment	-30°C ~ 50°C , 10% ~ 90% humidity



DIMENSIONS

